

## TEGERA® 295

Leather glove, 0,7-0,8 mm full grain goatskin, spandex, Thinsulate® 40g, Cat. II, white, grey, blue, waterproof, winter-lined, elasticated 360°, for allround work

### PROPERTIES

Extremely good fingertip sensitivity, extra flexible, durable, good grip, perfect fit, extra comfortable, warm

### SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE 6, 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,7-0,8 mm

BACK MATERIAL Spandex

LINING MATERIAL Thinsulate® 40g

CLO LINING 0,7 m<sup>2</sup>-K/W

DEXTERITY 5

FASTENING Elasticated 360°

COLOUR White, grey, blue

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Leather, elastane, polyester, natural latex

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Polyester



AQUATHAN®



Thinsulate  
INSULATION

SIZE	ART. NO.	EAN NO.
6	295-6	7340118313061
7	295-7	7340118313092
8	295-8	7392626034181
9	295-9	7392626034198
10	295-10	7392626034204
11	295-11	7392626034211
12	295-12	7392626037281

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 295

### FEATURES

Reinforced fingers and thumb, waterproof

### PRIMARY PROTECTION

Prevents risk of, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with moisture, contact with damp, contact with cold

### PRIMARY ENVIRONMENTS OF USE

Cold environments, wet environments

### PRIMARY AREAS OF USE

Machine operating, building and construction, carpentry, installation work, HVAC installation, soil preparation, transport work, machine driving, airport work, wood industry work, forest work, agricultural work, gardening, repair work

### PRIMARY INDUSTRIES OF USE

Transportation, utilities, building and construction, logistics

### TYPE OF WORK

Medium weight



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-08-24

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## TEGERA® 295

### EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

### COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 511:2006 Protective gloves against cold



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-08-24

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com